CLAIMS

1. Method for simulating a communications network through objects (13) that model a respective set of network modules or devices, characterised in that it comprises the step of inserting for every module or device of said set at least one respective interfacing object (13a', 13a''; 121b, 122b, 123b, 124b, 125b) with other modules or devices of said set; said respective interfacing object (13a', 13a''; 121b, 122b, 123b, 124b, 125b) having an external side (A) and an internal side (B) with respect to the module or device, said external side (A) of said respective interfacing object (13a', 13a''; 121b, 122b, 123b, 124b, 125b) being uniform for all modules or devices of said set.

2. Method according to claim 1, characterised in that it comprises the steps of:

- realising, for a module or device of said set, a plurality of different implementations (13b'; 13c'; 13b'', 13c'', 13d''), and

- providing a unique interfacing object (13a'; 13a'') for all different implementations of said plurality.

3. Method according to claim 1, characterised in that it comprises the steps of:

- realising, for a module or device of said set, a plurality of different implementations (121a, 122a; 123a, 124a; 125a), and

- providing a respective interfacing object (121b, 122b; 123b, 124b, 125b) for every different implementation of said plurality of different implementations.

4. Method according to claim 1, characterised in that it comprises the step of configuring the external side (A) of said interfacing objects to allow the

communication among modules or devices of said set as events (200; 1000, 1010, 1020).

5. Method according to claim 1, characterised in that it comprises the step of configuring the external side (A) of said interfacing objects to allow the communication among modules or devices of said set as messages (110, 120; 2000, 2010).

6. Method according to claim 1, characterised in that it comprises the steps of:

- providing a statistics managing module (11d) to collect statistic data pertaining to the operation of said simulated network, and

- measuring said statistic data through said statistics managing module (11d) through the external side (A) of said interfacing objects (121b, 122b; 123b, 124b, 125b) associated to the modules or devices (121, 123) of said set.

7. Method according to claim 1, characterised in that the external sides (A) of said interfacing objects exchange information with homologous objects associated with modules or devices of said set through structures comprising:

- an indicator of the source module or device (S),

- an indicator (110) of the target module or device, and

- the exchanged information (120).

8. Method according to claim 1, characterised in that said interfacing objects exchange information with homologous objects associated to the modules or devices of said set through structures comprising:

- an indicator of the source module or device (S),

- a time indicator (210),

- an indicator of the target module or device (220), and

- the exchanged information (230).

9. Method according to claim 1, characterised in that said interface objects comprise functionalities chosen from the group composed of:

- messages dispatching functionality (3060),

5 - events dispatching functionality (3020, 3040),

- messages receiving functionality (3050), and

- events receiving functionality (3010, 3030).

10. System for simulating a communications network through objects (13) that model a respective set of

10 network modules or devices, characterised in that the system includes, for every module or device of said set, at least one respective interfacing object (13a', 13a''; 121b, 122b, 123b, 124b, 125b) with other modules or devices of said set; said respective interfacing

15 object (13a', 13a''; 121b, 122b, 123b, 124b, 125b) having an external side (A) and an internal side (B) with respect to the module or device, said external side (A) of said respective interfacing object (13a', 13a''; 121b, 122b, 123b, 124b, 125b) being uniform for

20 all modules or devices of said set.

11. System according to claim 10, characterised in that it comprises:

- for at least one module or device of said set, a plurality of different implementations (13b'; 13c';

25 13b'', 13c'', 13d''), and

- a unique interfacing object (13a'; 13a'') for all different implementations of said plurality of different implementations.

12. System according to claim 10, characterised in

30 that it comprises:

- for at least one module or device of said set, a plurality of different implementations (121a, 122a; 123a, 124a, 125a), and

- a respective interfacing object (121b, 122b; 123b, 124b, 125b) for every different implementation of said plurality of different implementations.

13. System according to claim 10, characterised in that the external side (A) of said interfacing objects is configured for allowing the communication among modules or devices of said set as events (200; 1000, 1010, 1020).

14. System according to claim 10, characterised in that the external side (A) of said interfacing objects is configured for allowing the communication among modules or devices of said set as messages (110, 120; 2000, 2010).

15. System according to claim 10, characterised in that it comprises a statistics managing module (11d) to collect statistic data pertaining to the operation of said simulated network and in that said statistics managing module (11d) is configured for measuring said statistic data through the external side (A) of said interfacing objects (121b, 122b; 123b, 124b, 125b) associated to the modules or devices (121, 123) of said set.

16. System according to claim 10, characterised in that the external side (A) of said interfacing objects is configured for exchanging information with homologous objects associated to the modules or devices of said set through structures comprising:

- an indicator of the source module or device (S),
- an indicator (110) of the target module or device, and
- the exchanged information (120).

17. System according to claim 10, characterised in that the external side (A) of said interfacing objects is configured for exchanging information with

homologous objects associated to the modules or devices
of said set through structures comprising:

- an indicator of the source module or device (S),
- a time indicator (210),
- an indicator of the target module or device
(220), and
- the exchanged information (230).

18. System according to claim 10, characterised in
that said interface objects comprise functionalities
chosen from the group composed of:

- messages dispatching functionality (3060),
- events dispatching functionality (3020, 3040),
- messages receiving functionality (3050), and
- events receiving functionality (3010, 3030).

19. Object (13) of a system for simulating
telecommunications networks according to one any of
claims 10 to 18, characterized in that it comprises at
least one respective interfacing object (13a', 13a'';
121b, 122b, 123b, 124b, 125b) having an external side
(A) and an internal side (B) with respect to the
modelled module or device, said external side (A) of
said respective interfacing object (13a', 13a''; 121b,
122b, 123b, 124b, 125b) having a character that is
independent from idiosyncrasies of said module or
device.

20. Computer program product that is adapted to be
loaded in the memory of at least one computer and
comprising portions of software code to perform the
method according to one any of claims 1 to 9.